

Hand Control **RHC10**



The REAC Hand Control - RHC10 is a compact and flexible multi-channel hand control unit, which can be equipped with up to 10 buttons and 10 LED indicators. The buttons and LEDs can be combined in many combinations to fit your application requirements. With a customized top foil the hand control can be designed for your unique application.

RHC10 has as standard:

- Up to 4 channel buttons in two directions
- Charge level indicator
- Battery level indicator
- On/off switch with power indicator.
- Alert Indicator

RHC10 is compatible with REAC RCB10.

Standard features

Controls	1 – 4 channels, individual actuators
Protection class	IPX4
LED indicator	Charge level Battery level Alert
Power on/off switch	Yes
Key locking function	Yes*
Activation	Hold to run
Top foil	REAC design
Mounting	Hook
Operating temperature	-25°C to +50 °C
Storage temperature	-40°C to +70 °C
Color	Black and orange
EMC conformity	EN 61000-6-2 EN 61000-6-3 EN 60601-1-2 ISO 7176-21

** A key lock function to lock one or several channels is available. To lock a channel press both buttons for that channel at the same time for 3 seconds until the alert indicator LED is lit. Channel is locked. If turning off the system with the on/off button and then start again, the red LED will lit for a short while to indicate that a key lock is active. To unlock the same procedure is used, i.e. press both channel buttons at the same time for 3 seconds until the alert indicator LED is switched off.*

Options

LED indicators	Customized usage and number (between 0-10)
Buttons	Customized usage and number (between 1-10)
Top foil	Customized design
Mounting	Magnet
Color	Customized
Sound alarms	Yes

Dimensions



© REAC, April 2019, Issue 3.0

REAC is continuously developing our products and can make changes without prior notice. Therefore we can't guarantee that the information stated on our webpage or in our written material always is up to date, nor can we take responsibility for any misinterpretation of our written context. Technical specification might change due to load and external circumstances. REAC products shall be tested in its intended application before use.

REAC AB
Forsbrogatan 4
662 34 Åmål, Sweden

REAC Poland Sp. z o.o
Ul. Sulejowska 45
97-300 Piotrków Trybunalski, Poland

www.reac.se
E-mail: info@reac.se
Phone: +46 532 78 50 00